



BALERS

M70MB MINI BALER

SINCE 1968

BPI

Manufacturing

CUSTOM SOLUTIONS





BALERS

M70MB MINI BALER

TECHNICAL SPECIFICATIONS

The M70MB has been developed for the smaller farmer and can be trailed by low kilowatt tractors rated as low as 20 kW. Tractors with low kilowatt normally do not have hydraulic systems and therefore the Mini Baler comes with its own hydraulic pump and is driven by the tractor's PTO. If the tractor used has its own hydraulic system, the bale chamber can be opened and closed from the tractor's seat, which will enable the baler to work faster and achieve higher production rates per day. The compression bale chamber and the wrapping and compression system, consists of drive chains and cross bars and enables the packaging of all types of green or dry crop. When the bale chamber is full, a buzzer will alarm the operator that the chamber is full and the operator will activate the automatic mono twine binder. Their compact nature and size allow for easy transportation and storage. Bale weights can be controlled by adjusting the bale density setting and the three-point hitch allows for easy lifting and manoeuvring on small fields. The Mini Round Baler is the economical choice for producing bales that are easy to handle, transport and store. They are also great for producing bales of wet or any other forage. The mini baler is an excellent choice for small farmers.

STOCK CODE	NUMBER OF COMPACTING ROLLERS	NUMBER OF BALES PER HOUR	TOTAL LENGTH	TOTAL WIDTH	TOTAL HEIGHT	BALER PICK-UP	POWER REQUIRED	TOTAL WEIGHT
M70MB	8 PIECES	50-80	1 350 mm	1 350 mm	1 400 mm	800 mm	20-35 kW	440 kg

* Manufacturer reserves the rights to change the above without any notice.